NOTES:


- ALLOWABLE OPTICAL MATERIAL: SCHOTT: Fused Silica 458/678
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO < 3 ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE)


\$1: ENHANCED ALUMINUM Ravg ≥ 95% 450-650nm @ 0° AOI

S2: NONE

4.\ ARROW ON EDGE POINTING TOWARDS SURFACE \$1.

5. FINE GROUND SURFACE





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

	\$1	S2	EFL (AT 587.6nm)	NA	Edmund Optics ®	
SHAPE	PLANO	PLANO				
SURFACE ACCURACY AT 632.8nm	1/10 WAVE	NA	BFL (AT 587.6nm)	NA		
SURFACE QUALITY	60 - 40	COMMERCIAL POLISH			TITLE	1/10λ Optical Flat, Fused Silica, 12inch Diameter ENHANCED ALUMINUM
CLEAR APERTURE	Ø 274.3	Ø274.3	ALL DIMS IN	mm	DWG NO	69921-533
BEVEL MAX FACE	1.0 x 45°	1.0 x 45°				