NOTES: 1. SUBSTRATE: FUSED SILICA


2. COATING (APPLY ACROSS CLEAR APERTURE)


\$1: NONE \$2: NONE

- 3. EDGES: FINE GROUND
- 4. CENTERING: <3-5 ARCMIN
- 5. ASPHERE FIGURE ERROR: 0.75µm µm RMS



 $Z_{ASPH}(Y) = \frac{(\frac{1}{RADIUS})*Y^{2}}{1 + \sqrt{1 - (1+k)*(\frac{1}{RADIUS})^{2}*Y^{2}}} + D*Y^{2} + E*Y^{4} + F*Y^{6} + G*Y^{8} + H*Y^{10} + J*Y^{12} + L*Y^{14}$





COEFFIECIENT TABLE 7

\$1 -1.099272E+00

0.000000E+00

1.094492E-05

9.288686E-09

-5.645807E-12

1.501010E-14 0.000000E+00

0.000000E+00

COEFFIECIENT

k

D E

F

G

Н

J

L

FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

REV. A	S1	\$2	EFL @ 587.6nm	40		Edmund Optic	N R
SHAPE	CONVEX	PLANO	BFL @ 587.6nm	21.15			ر ک
RADIUS	18.339	INFINITY		I		50mm DIA 0.63 NA UNCOATED, UV FL	ISED
SURFACE QUALITY	60-40	60-40			TITLE	SILICA ASPHERIC LENS	
CLEAR APERTURE	90%	90%					
BEVEL MAX	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	67266	SHEET 1 OF 1