NOTES:


1. SUBSTRATE MATERIAL: FLOAT GLASS


2. COATING (APPLOW ACROSS CLEAR APERTURE): \$1: BARE ALUMINUM \$2: NONE


3. BLAZE ANGLE: 17° 27' NOMINAL BLAZE WAVELENGTH: 500nm EFFICIENCY: 60-80% @ BLAZE WAVELENGTH



5. Rohs Compliant







FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

| | Edmund | Optics® |
|--|--------|---------|
| | | |

| | | | | 1 | | GRATING DIFF 1200GR 500nm 12.5 x 25 | |
|----------------|--------------|--------------|------------------------|----|--------|---|-----------------|
| | \$1 | \$2 | THIRD ANGLE PROJECTION | | TITLE | OK/ (1114 O DIT 1200 OK 3001111 12.3 x 20 | |
| SHAPE | PLANO | PLANO | | | | | CUEET |
| CLEAR APERTURE | 11.25 x 22.5 | 11.25 x 22.5 | ALL DIMS IN | mm | DWG NO | 43004 | SHEET 1 OF 1 |