
NOTES:


- 1. SUBSTRATE: CRYSTAL QUARTZ
- COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(abs) <0.25% @ 488nm DAMAGE THRESHOLD: 3.5 J/cm² @10ns @ 1064nm


FOR INFORMATION ONLY: DO NOT MANUFACTURE


PARTS TO THIS DRAWING

- 3. SURFACE \$1 TO BE PARALLEL TO SURFACE \$2 TO WITHIN <0.5 arcsec
- 4. RETARDANCE: $\lambda/2 \pm \lambda/200$
- 5. TRANSMITTED WAVEFRONT: λ /10 FOR CENTRAL 80% OF CLEAR APERTURE
- 6. RoHS COMPLIANT









SECTION A-A

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

					GO [®] Edmund Optics [®]		
	<u>\$1</u>	\$2 (78.0		TITLE	12.7mm DIA. 488nm λ/2 QUARTZ WAN ZERO ORDER	/EPLATE	
CLEAR APERTURE SURFACE QUALITY	Ø8.0 10-5	Ø8.0 10-5	ALL DIMS IN mm	DWG NO	85034	Sheet 1 Of 1	