
NOTES:


- 1. SUBSTRATE: FUSED SILICA
- 2. S2 TO BE PARALLEL TO S1 TO WITHIN <3ARCMIN
- COATING (APPLY ACROSS COATING APERTURE)
 \$1: EN AL
 R(AVG) >95% from 450-650nm

S2: NONE



- 5. CLEAR APERTURE AND COATING APERTURE ARE CENTERED ON SURFACE
- 6. SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 7. ROHS: COMPLIANT





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	S2						
SHAPE	PLANO	PLANO	1			[®] Edmund	Ontic	CR
SURFACE QUALITY	20-10	COMMERCIAL POLISH			U		Optic	, 5 °
SURFACE FLATNESS	0.10 WAVE	N/A	THIRD ANGLE PROJECTION		TITLE	MIRROR FS 1/10 WAVE EN AL 6.35 DIA		
CLEAR APERTURE	Ø5.40	N/A						1/1
COATING APERTURE	Ø5.35	N/A		 			ı	CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	39189		SHEET 1 OF 1