



FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING









-	5.00±0.10

R	Δ	N	\Box	Ρ.	Δ	SS	FI	17	ΓFΙ	5
u	$\overline{}$	ıν	ப		\neg	ധ	1 1	_	பட	`

REV. 001	VALUE
CENTER WAVELENGTH (CWL)	343nm ±2nm
FULL WIDTH HALF MAX (FWHM)	10.0 ±2nm
MINIMUM TRANSMISSION	≥85%
BLOCKING	200 - 1200nm
SURFACE QUALITY	80-50
CONSTRUCTION	MOUNTED IN BLACK ANODIZED ALUMINUM RING
COATING TYPE	Hard Coated
DURABILITY	MIL-C-48497a, SEC 3.4.1
ENVIRONMENTAL	MIL-STD-810F, SEC 507.4

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

ED ® Edmund Optics®

<u>3</u>	THIRD ANGLE PROJECTION	TITLE	Filter BP 343 x 10nm OD4 25n	nm
	ALL DIMS IN mm	DWG NO	39314	SHEET 1 OF 1