


## NOTES:

- 1. SUBSTRATE: UV GRADE FUSED SILICA
- 2. COATING (APPLY ACROSS CLEAR APERTURE) S1 & S2: R(ABS) < 0.25% @ 532nm R(ABS) < 0.25% @ 1064nm R(AVG) < 1.0% @ 500 - 1100nm
- 3. SURFACE S2 TO BE PARALLEL WITH S1 TO <5 ARCSEC
- 4. FINE GRIND SURFACE
- 5. Rohs Compliant







## PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2		
SHAPE	PLANO	PLANO		
SURFACE QUALITY	20-10	20-10		
CLEAR APERTURE	Ø20.00	Ø20.00		
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED		

			Edmund Optics®		
THIRD ANGLE PROJECTION	$\phi \lhd$	TITLE	25mm DIA., 3mm THICK, YAG-BBAR CC λ/10 FUSED SILICA WINDOW	ATED,	
ALL DIMS IN	mm	DWG NO	13355	SHEET 1 OF 1	

25mm DIA., 3mm THICK, YAG-BBAR COATED,
λ/10 FUSED SILICA WINDOW

L DIMS IN mm DWG NO 13355	l DIMS IN	mm	DWG NO	13355	SHEI 1 OI
---------------------------	-----------	----	--------	-------	--------------