

## NOTES:

- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO < 1ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(AB\$) < 0.25% @ 532nm @ 0° AOI R(ABS) < 0.25% @ 1064nm @ 0° AOI R(AVG) < 1.0% FROM 500-1100nm @ 0° AOI



5. Rohs Compliant





## **PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE (mm)	Ø11.43	Ø11.43
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

			Edmund Optic	S®
THIRD ANGLE - PROJECTION	<b>\$</b>	TITLE	12.7mm DIA., 3mm THICK, YAG-BBA COATED λ/4 N-BK7 WINDOW	\R
ALL DIMS IN	mm	DWG NO	15791	SHEET 1 OF

SHEET 1 OF 1