
NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO < 1ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(ABS) <0.25% @ 532nm R(ABS) <0.25% @ 1064nm R(AVG) <1.0% @ 500 - 1100nm



5. Rohs Compliant

6. SURFACE FLATNESS (P-V): λ/4 (per inch over clear aperture)







SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE (mm)	Ø22.86	Ø22.86
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

THIRD ANGLE PROJECTION	ϕ	TITLE
ALL DIMS IN	mm	DWG

ĸ	Edmund Optics®
	25.4mm DIA., 2mm THICK, YAG-BBAR
	COATED, \(\lambda/4\) N-BK7 WINDOW

L DIMS IN mm DWG NO 15792 SHEET 1 OF 1