
## NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO < 1ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(ABS) <0.25% @ 532nm R(ABS) < 0.25% @ 1064nm R(AVG) <1.0% @ 500 - 1100nm




5. Rohs Compliant

6. SURFACE FLATNESS (P-V): λ/4 (per inch over clear aperture)







## **PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE (mm)	Ø45.72	Ø45.72
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

THIRD ANGLE PROJECTION	$\phi$	TITLE
ALL DIMS IN	mm	DWG

50.8mm DIA., 4mm THICK, YAG-BBAR

1 OF 1

OJECTION	<del>\ \ \ \ \ \</del>	IIILE	COATED, λ/4 N-BK7 WINDOW	
ll DIMS IN	mm	DWG NO	15794	SHEET