NOTES:


- 1. SUBSTRATE: HOYA GLASS: ND-0.3
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN <0.02mm

3. FINE GRIND SURFACE


- 4. COATING SPECIFICATION: S1 & S2:R(AVG) ≤0.5% @ 600 - 1050nm
- 5. OPTICAL DENSITY: 3 +/-0.3 @ 400-700nm
- 6. TRANSMISSION (%): 0.1% AVERAGE FROM 400-700nm
- 7. ROHS COMPLIANT


NEUTRAL DENSITY FILTER

Т



DO





R

FORMATION ONL

PARTS TO THIS DRAWING

ANUFACTURE

## SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

			_		B	Edmund Opt	CS®
	S1	S2			TITLE DWG NO	3.0 OD, 50mm DIA., NIR I COATED, ABSORPTIVE ND FILTER	
SHAPE	PLANO	PLANO	THIRD ANGLE . PROJECTION	$\odot$			
SURFACE QUALITY	80-50	80-50	T				
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm		13194	SHEET 1 OF 1
		·				·	· · · ·