

0.19 - 20µm, 3W, Thermopile Power Detector



0.19 - 20µm, 3W, Thermopile Power Detector

Stock **#78-464** **1 In Stock**

⊖ 1 ⊕ £1,692⁰⁰

ADD TO CART

Volume Pricing

Qty 1-4	£1,692.00 each
Qty 5+	£1,520.00 each
Need More?	Request Quote

ⓘ Prices shown are exclusive of VAT/local taxes

Product Downloads

Maximum Incident Energy Density (J/cm², 10ns Pulses):

1

General

Model Number:
XLP12-3S-H2-INT-D0

Cooling Method:
Convection

Compatible Meters:

Physical & Mechanical Properties73 x 73 x 20 **Dimensions (mm):**310 **Weight (g):**0.31 **Weight (kg):**12 **Active Area (mm):****Optical Properties**190 - 20000 **Wavelength Range (nm):**0.19 - 20 **Wavelength Range (μm):****Sensor**Thermopile **Type of Sensor:****Electrical**3,000 **Maximum Incident Beam Power (mW):**3 **Maximum Incident Beam Power (W):**1,000 **Maximum Incident Power Density (W/cm²):**1 **Maximum Incident Power Density (kW/cm²):**0.5 μW **Noise Level:****Regulatory Compliance**[View](#) **Certificate of Conformance:****Product Details**

- Photodetectors, Thermopiles, and Pyroelectric Detectors Available
- Various Active Area Sizes Across a Wide Range of Sensitivities
- [Meterless](#) and [Wireless](#) Detectors Also Available

Gentec-EO Integra USB Power and Energy Detectors combine a power meter and detector in one convenient package while providing fast response times and accurate measurements for beam analysis. These detectors are designed with a USB connector for easy connection to a PC or other acquisition system and include user-friendly software allowing for control via PC or serial commands. Versatile pyroelectric energy detectors with broadband coatings are optimized for low to high power densities. Gentec-EO Integra USB Power and Energy Detectors can be used with a variety of laser powers ranging from the nanowatts to multi-kilowatts. These detectors are ideal for laser energy measurement, thermal imaging, and remote sensing applications.