

**TECHSPEC® 0.9X, 28.7mm F-Mount PlatinumTL™ Telecentric Lens**



0.9X Magnification

Stock **#62-902** **4 In Stock**

⊖ 1 ⊕ £2,044<sup>00</sup>

**ADD TO CART**

Volume Pricing

Qty 1+	£2,044.00 each
Need More?	<a href="#">Request Quote</a>

ⓘ Prices shown are exclusive of VAT/local taxes

Product Downloads

**General**

PlatinumTL™ Series **Series:**

**Stock No. of Mounting Clamp:**  
[#56-025](#) Sold Separately

Telecentric Lens **Type:**

**Physical & Mechanical Properties**

**Iris Option:**


Variable	
170.80	Length (mm):
65.0	Maximum Diameter (mm):
786	Weight (g):
46.5	Flange Distance (mm):
<b>Optical Properties</b>	
24.9mm	Horizontal Field of View, APS-C Sensor:
31.9mm	Field of View, 28.7mm Sensor:
19.2mm	Horizontal Field of View, 4/3" Sensor:
15.8mm	Horizontal Field of View, 1.1" Sensor:
14.2mm	Horizontal Field of View, 1" Sensor:
9.8mm	Horizontal Field of View, 2/3" Sensor:
7.1mm	Horizontal Field of View, 1/2" Sensor:
27.90	Maximum Image Circle (mm):
0.075	Numerical Aperture NA, Object Side:
10 (7)	Number of Elements (Groups):
<0.070	Typical Telecentricity @ 588nm (°):
<0.035	Typical Distortion @ 588nm (%):
0.9X	Primary Magnification PMAG:
0.90	Telecentric Lens Magnification:
111.00	Working Distance (mm):
24.9 x 18.7	FOV @ Max Sensor Format, H x V (mm):
f/6 - f/22	Aperture (f/#):
425 - 675nm BBAR	Coating:
±0.65 at f/10 (20% @ 20 lp/mm)	Depth of Field (mm):
0.9X	Magnification:
VIS	Lens Wavelength Range:
<b>Sensor</b>	
APS-C	Maximum Sensor Format:
2.74	Pixel Size (µm):
<b>Threading &amp; Mounting</b>	
M62 x 0.75 (Female)	Filter Thread:
F-Mount	Mount:
<b>Regulatory Compliance</b>	
<a href="#">View</a>	Certificate of Conformance:

## Product Details


- High Resolution f/6 Bi-Telecentric Lens for Measurement
- Up to 35 MegaPixels, 2.8µm Pixel Size Sensors
- APS-C, C-Mount, T-Mount, F-Mount Telecentric Lens
- Magnification from 0.28X to 1.7X

TECHSPEC® PlatinumTL™ Telecentric Lenses are designed for semiconductor and electronics inspection, measurement, and gauging applications. The precision designs feature high telecentricity (<math><0.1^\circ</math>), low distortion (<math><0.1\%</math>), and high light throughput with an adjustable aperture that achieves f/6 when fully open. Capable of supporting large format 28.7mm diagonal sensors, these lenses are compatible with the Sony IMX342 APS-C sensor and other similar format sensors such as the Sony IMX530. TECHSPEC® PlatinumTL™ Telecentric Lenses produce unparalleled levels of contrast yielding maximum image quality with the highest degree of measurement accuracy. These lenses are suitable for high vibration environments and feature a removable recessed set screw for securing the iris in place.


## Technical Information




#62-902, 0.9X, 28.7mm F-Mount PlatinumTL™ Telecentric Lens, Distortion Plot



#62-902, 0.9X, 28.7mm F-Mount PlatinumTL™ Telecentric Lens, Relative Illumination Plot




#62-902, 0.9X, 28.7mm F-Mount PlatinumTL™ Telecentric Lens, Telecentricity Plot




#62-902, 0.9X, 28.7mm F-Mount PlatinumTL™ Telecentric Lens, Modulated Transfer Function (MTF) Plot, 111mm Working Distance, f6



#62-902, 0.9X, 28.7mm F-Mount PlatinumTL™ Telecentric Lens, Depth of Field Plot, 111mm Working Distance, f6



#62-902, 0.9X, 28.7mm F-Mount PlatinumTL™ Telecentric Lens, Modulated Transfer Function (MTF) Plot, 111mm Working Distance, f10



#62-902, 0.9X, 28.7mm F-Mount PlatinumTL™ Telecentric Lens, Depth of Field Plot, 111mm Working Distance, f10

Description		Stock No.	Flange	Length (A)	Front Diameter (B)	Back Diameter (C)
0.28X	C-Mount	#62-933	17.5mm	230.8mm	60.5mm	33.5mm
0.5X	C-Mount	#62-932	17.5mm	174.9mm	50mm	33.5mm
1.7X	C-Mount	#63-232	17.5mm	189.5mm	60mm	46mm
0.28X	F-Mount	#62-922	46.5mm	167.6mm	138.6mm	55mm
	M42 x 1.0	#62-923	6.56mm	208.5mm	138.6mm	50mm
	M42 x 1.0	#62-924	19.53mm	195.5mm	138.6mm	50mm
0.5X	F-Mount	#62-912	46.5mm	143mm	90mm	55mm
	M42 x 1.0	#62-913	6.56mm	184mm	90mm	50mm
	M42 x 1.0	#62-914	19.53mm	171.1mm	90mm	50mm
0.9X	F-Mount	#62-902	46.5mm	170.8mm	65mm	55mm
	M42 x 1.0	#62-903	6.56mm	210.7mm	65mm	53mm
	M42 x 1.0	#62-904	19.53mm	197.8mm	65mm	53mm

