TECHSPEC® 6.25mm Inner Single Optic Mount

6.25mm Inner Single Optic Mount

Stock **#38-746** **6 In Stock**

- 1 + **£29.77**

ADD TO CART

Volume Pricing	
Qty 1-4	**£29.77** each
Qty 5+	**£28.27** each
Need More?	Request Quote

Prices shown are exclusive of VAT/local taxes

Product Downloads

SPECIFICATIONS

General

Type:
Fixed

Function:

Optic Mount (Fixed)

Physical & Mechanical Properties

Construction:
Matte Black Anodized Aluminum (6061-T6)

Total Length (mm):
9.0

Clear Aperture CA (mm):
5.2

Max. Thickness of Compatible Optics (mm):
4.0

Min. Thickness of Compatible Optics (mm):
1.0

Edge Thickness of Compatible Optics (mm):
4.0

Threading & Mounting

Diameter of Compatible Optics (mm):
6.25

Thread Type:
M29 x 0.75

Regulatory Compliance

RoHS 2015:
Compliant

Certificate of Conformance:
View

PRODUCT DETAILS

- Mounts for a Variety of Optical Component Diameters and Thicknesses
- M29 Outer Diameter Threads Allow Easy Positioning Within **Outer Tubes**
- One Retainer Ring and One Delrin Ring are Included
- Click **Here** to See How to Use the Multi-Element Tube System Components to Build an Optical System.

TECHSPEC® Multi-Element Inner Single Optic Mounts are designed to mount a variety of optical components. The mounts support optical diameters from 5mm to 25.4mm, and edge thicknesses of 4mm to 17mm. With M29 x 0.75 outer diameter threads, these mounts can be easily positioned along the optical axis of our TECHSPEC® Multi-Element Outer Tubes. TECHSPEC® Multi-Element Inner Single Optic Mounts include one Delrin ring to ensure secure clamping force between the retainer ring and optic without damaging the optic.

Note: Our specially designed ME Spanner Wrench (**#13-567**) is highly recommended to move Inner Single Optic Mounts back and forth smoothly utilizing a combined metric and English graduated scale. The hollow design enables transmission of output beam while adjusting lens position. Non-scaled ME Spanner Wrench (**#11-046**) is also available.