

[See all 71 Products in Family](#)

## Basler ace acA4096-11gc Color GigE Camera

See More by [Basler](#)



Basler ace GigE Cameras



Stock **#37-210** **1 In Stock**

[Similar Cameras](#)

⊖ 1 ⊕ £1,360<sup>00</sup>

**ADD TO CART**

### Volume Pricing

Qty 1+	£1,360.00 each
Need More?	<a href="#">Request Quote</a>

ⓘ Prices shown are exclusive of VAT/local taxes

### Product Downloads

Color

Spectrum:

### General

Color Camera

Type:

Model Number:

**Manufacturer:**  
Basler

**Camera Series:**  
ace

## Physical & Mechanical Properties

**Dimensions (mm):**  
50 x 40 x 30 (excludes connectors and lens mount)

**Weight (g):**  
90

**Housing:**  
Full

## Sensor

**Sensor Format:**  
1"

**Resolution (Megapixels):**  
9.00

**Frame Rate (fps):**  
12.00

**Pixels (H x V):**  
4,096 x 2,160

**Pixel Size, H x V (µm):**  
3.45 x 3.45

**Sensing Area, H x V (mm):**  
14.13 x 7.45

**Imaging Sensor:**  
Sony IMX267

**Type of Sensor:**  
Progressive Scan CMOS

**Shutter Type:**  
Global

**Pixel Depth:**  
10/12 bit

**Exposure Time:**  
Programmable via camera API, hardware trigger

**Dynamic Range (dB):**  
Not Specified

**Machine Vision Standard:**  
GigE Vision, GenICam

## Electrical

**Power Consumption (W):**  
2.7 (12VDC External Power Supply)  
3.2 (PoE)

## Hardware & Interface Connectivity

**Interface:**  
GigE (PoE)

**Connector:**  
GigE, RJ45 with Screw Locks

**Power Supply:**  
Power Supply Required and Sold Separately:  
USA: [#68-466](#)  
Europe: [#68-466](#)  
Japan: [#68-466](#)  
Korea: [#68-466](#)  
China: [#68-466](#)

**GPIOs:**  
1 opto-coupled input line, 1 opto-coupled output line,  
1 general purpose I/O (GPIO) line

**Synchronization:**  
Hardware Trigger (GPIO), Software Trigger, or Free-Run

**Interface Port Orientation:**  
Back Panel

**GPIO Connector Type:**  
6-pin Hirose (HR10)

## Threading & Mounting

**Mount:**  
C-Mount

**Mounting Threads:**  
1/4-20 with Tripod Mount Adapter [#17-711](#)

## Environmental & Durability Factors

**Operating Temperature (°C):**

0 to +50

Storage Temperature (°C):

-20 to +80

## Regulatory Compliance

[Compliant](#)

RoHS 2015:

[View](#)

Certificate of Conformance:

[Compliant](#)

Reach 235:

## Product Details

- Perfect Analog Replacement
- Ultra-Small Form Factor
- Power Over Ethernet (PoE)
- Includes Basler Pylon Driver

Basler ace GigE Cameras are economical Gigabit Ethernet cameras that provide an ideal upgrade opportunity for analog camera users. With a small form factor matching that of many analog cameras (29 x 29mm), the ace can be a drop-in replacement to an existing analog system or a great choice to start a new project. Basler ace GigE Cameras can use Power Over Ethernet (PoE) (2 GigE cables required). The cameras can have long cable lengths and are the optimal choice for use on a factory floor. All cameras include the industry-proven Basler Pylon SDK Software and Driver.

## Technical Information



MT9P031 Sensor QE Curve