

TECHSPEC®

Fluorescence Filter Set for Green Fluorescence Protein (GFP)



Fluorescence Filter Sets



Stock **#67-003** 1 In Stock

-

1

+

£760<sup>00</sup>

ADD TO CART

| Volume Pricing |                               |
|----------------|-------------------------------|
| Qty 1-9        | £760.00 each                  |
| Qty 10-25      | £684.00 each                  |
| Qty 26-49      | £616.00 each                  |
| Need More?     | <a href="#">Request Quote</a> |

Prices shown are exclusive of VAT/local taxes

Product Downloads

General

Type:

Fluorescence Filter Kit

Compatible Fluorophore:

GFP

|         |                    |
|---------|--------------------|
| #67-027 | Excitation Filter: |
| #67-030 | Emission Filter:   |
| #67-079 | Dichroic Filter:   |

Optical Properties

|                             |                                     |
|-----------------------------|-------------------------------------|
| Fused Silica (Corning 7980) | Substrate: <input type="checkbox"/> |
| Hard Coated                 | Coating:                            |
| 457 - 487                   | Excitation Wavelength (nm):         |
| 502 - 538                   | Emission Wavelength (nm):           |
| 495.00                      | Dichroic Cut-On Wavelength (nm):    |
| 457 - 538                   | Wavelength Range (nm):              |

Regulatory Compliance

|      |                             |
|------|-----------------------------|
| View | Certificate of Conformance: |
|------|-----------------------------|

## Product Details


- Excitation, Emission, and Dichroic Filters for Fluorescence Imaging
- >93% Transmission and OD 6 Blocking for Maximum Brightness and Contrast
- Hard Sputtered Coatings on Single Substrate
- TECHSPEC Pre-Mounted Filter Cubes Also Available

Our TECHSPEC® Fluorescence Filter Sets are designed to provide brilliant images when integrated into a fluorescence microscope. The high transmission of the bandpass filters guarantees the brightest possible images, while the deep blocking ensures no unwanted light gets to the detector. This ensures images will be brighter and will have much greater signal-to-noise than what is commonly available with soft coated, evaporated filters. TECHSPEC Fluorescence Filter Sets are ideal for fluorescence microscopy or fluorescence imaging applications and are available for common fluorescent dyes and fluorescent proteins. Additionally these filters are also used in polymerase chain reaction (PCR) diagnostic instruments.

Fluorescence filter sets include an Excitation and Emission filter from our [TECHSPEC® Fluorescence Bandpass Filters](#) and a Dichroic filter from our [TECHSPEC® Dichroic Filters](#). Excitation filters are placed within the illumination path of fluorescence microscopes to pass only wavelengths within the excitation range of the fluorophore under inspection. Emission filters are placed within the imaging path of a fluorescence microscope to pass only wavelengths within the emission range of the fluorophore. Dichroic filters are placed in between the excitation filter and the emission filter to reflect the excitation signal towards the fluorophore while transmitting the emission signal to the detector.

Filter sets are listed with the most common fluorophores. For a full list of compatible fluorophores with each set, view [Fluorophores and Optical Filters for Fluorescence Microscopy](#). TECHSPEC Fluorescence Filter Sets are available pre-mounted in [Olympus or Nikon Filter Cubes](#).

## Technical Information



|                             | Excitation and Emission Filters                   | Dichroic Filter |
|-----------------------------|---------------------------------------------------|-----------------|
| Size                        | 25.0mm                                            | 25.2 x 35.6mm   |
| Thickness                   | 3.5mm                                             | 1.05mm          |
| Tolerances                  |                                                   |                 |
| Size                        | +0.0/-0.1                                         |                 |
| Thickness                   | ±0.1mm                                            |                 |
| Clear Aperture              | 22.0mm                                            | 22.0 x 30.0mm   |
| Transmitted Wavefront (RMS) | <λ/4                                              |                 |
| Angle of Incidence          | 0.0° ±5.0°                                        | 45.0° ±5.0°     |
| Compatible Microscopes      | Most common Nikon, Olympus, and Zeiss Microscopes |                 |

