

[See all 13 Products in Family](#)

# White, Low-Angle Square Light FPQ3-96SW

See More by [CCS](#)



Stock #21-810 **1 In Stock**

⊖ 1 ⊕ £1,304<sup>00</sup>

**ADD TO CART**

Volume Pricing	
Qty 1+	£1,304.00 each
Need More?	<a href="#">Request Quote</a>

⚠ Prices shown are exclusive of VAT/local taxes

## Product Downloads

### General

FPQ3-96SW **Model Number:**

LED Illuminator **Type of Illumination:**

CCS **Manufacturer:**

Low-Angle Square Light **Geometry:**

Constant **Illumination Mode:**

## Physical & Mechanical Properties

W 96 mm x D 96 mm x H 30 mm **Dimensions (mm):**

170 **Weight (g):**

## Optical Properties

White **Color:**

## Electrical

25 **Power Consumption (W):**

## Hardware & Interface Connectivity

24 **Input Voltage (V):**

**Power Supply:**  
Power Supply Required and Sold Separately.  
USA: [#73-491](#)  
Europe: [#73-491](#)  
Japan: [#89-513](#)  
Korea: [#33-773](#)  
China: [#73-491](#)

## Environmental & Durability Factors

6000 **Color Temperature (K):**

## Regulatory Compliance

[Exempt](#) **RoHS 2015:**

[Contains SVHC\(s\)](#) **Reach 224:**

[View](#) **Certificate of Conformance:**

## Product Details

- Improved Inspection of Rectangular and Square Objects vs. Ring Lights
- Low-Angle Lighting from Four Directions
- Ideal for Inspection of Food Packaging and PCB's

CCS Low-Angle Square LED Illuminators provide uniform diffuse illumination from a low angle in four directions. This low-angle square design helps to prevent glare and enables the detection of outlines and corners which is difficult to achieve with traditional ring lights. These lights feature mounting holes along the top and sides, allowing for flexibility with system installation. CCS Low-Angle Square LED Illuminators are ideal for embossed character recognition and inspection of square parts such as food packaging, circuit boards (PCB's), and print patterns.

**Note:** Power supply [#66-855](#) is required and sold separately.

## Technical Information

### Imaging Examples for the FPQ3-100X50 Light Unit

Illumination from a low angle clearly highlights the outline of workpieces.

