

Single Mode Patchcord, FC/APC, 0.13NA, 780-970nm, 1m



FC/APC Connector

Stock #25-942 4 In Stock


1 £94^{.40}

ADD TO CART

Volume Pricing	
Qty 1-4	£94.40 each
Qty 5-24	£84.80 each
Need More?	Request Quote

Prices shown are exclusive of VAT/local taxes

Product Downloads

-  STEP:step
-  EO Spec Sheet
-  [Download All](#)

General

Type: Patchcord	Fiber Cable Type: 780HP
------------------------	--------------------------------

Physical & Mechanical Properties

Cladding Diameter (µm): 125 ± 1.0	Length (m): 1
Jacket Material: 900µm Yellow Hytrel® Tubing	Coating Diameter: 245 ± 15µm

Optical Properties

Numerical Aperture NA: 0.13	Attenuation (dB/km): ≤3.5dB/km @ 780nm
Wavelength Range (nm): 780 - 970	Mode Field Diameter (nm): 5.0 ± 0.5µm @ 850nm

Hardware & Interface Connectivity

Connector: FC/APC	Insertion Loss (dB): 1.5 @ 780nm
--------------------------	-----------------------------------------

Regulatory Compliance

RoHS 2015: Compliant	Certificate of Conformance: View
REACH 241: Compliant	

Need different specs or modifications?

Edmund Optics offers comprehensive custom manufacturing services for optical and imaging components tailored to your specific application requirements. Whether in the prototyping phase or preparing for full-scale production, we provide flexible solutions to meet your needs. Our experienced engineers are here to assist—from concept to completion.

Our capabilities include:

- Custom dimensions, materials, coatings, and more

- High-precision surface quality and flatness
- Tight tolerances and complex geometries
- Scalable production—from prototype to volume

Learn more about our [custom manufacturing capabilities](#) or submit an inquiry [here](#).

Product Details

- FC/PC, FC/APC, and Hybrid Terminated Connectors
- Patchcords for Wavelengths from 450 – 1650nm
- 1m, 2m and 5m Standardized Lengths Available

Single Mode Fiber Optic Patchcords are available with FC/PC or FC/APC terminated connectors. Hybrid terminated connectors enable users to adapt FC/PC or FC/APC patchcords for compatibility with existing fiber assemblies. Designed for use with lasers from 450 – 1650nm in 1m, 2m and 5m standard lengths, these Single Mode Fiber Optic Patchcords are ideal for applications including beam delivery, microscopy, and telecommunications. Each connector is engraved with the fiber type for easy integration and identification.

Related Products



Polarization Maintaining Fiber Optic Patchcords



LightPath® Fiber Optic Collimators



Fiber Connector Adapters



Focusable Collimators

Frequently Purchased Together



#23-784 - 785nm 20mW Pigtailed Laser Diode
£688.00

Qty



#71-143 - Single Mode Patchcord, FC/APC, 0.13NA, 780-970nm, 5m
£107.20

Qty



#73-818 - 5V DC/2.4A Power Supply & Plug Adapters
£34.40

Qty

Resources

Media Type

- FAQ
- Glossary
- Technical Tool
- Video

? FAQ

What diameter beam will an optical fiber output?

? FAQ

What is the numerical aperture of a fiber?

? FAQ

Why do optical fibers lose so much energy?

? FAQ

What is the attenuation curve and how do I use it?

? FAQ

What is the difference between a jacketed and...

? FAQ

What is the difference between single-mode...

[View More](#)