

**TECHSPEC® Sliding 2" x 3" Base Plate**



Stock #03-655 **20+ In Stock**

⊖ 1 ⊕ £20<sup>00</sup>

**ADD TO CART**

Volume Pricing

Qty 1-9	£20.20 each
Qty 10+	£18.00 each
Need More?	<a href="#">Request Quote</a>

**!** Prices shown are exclusive of VAT/local taxes

Product Downloads

**General**

English Type:

**Physical & Mechanical Properties**

76.20 Length (mm):

50.80 Width (mm):

9.50                      **Thickness (mm):**

Black Anodized Aluminum                      **Construction:**

2                              **Number of Slots:**

## Regulatory Compliance

[Compliant](#)                      **RoHS 2015:**

[View](#)                              **Certificate of Conformance:**

[Compliant](#)                      **Reach 250:**

## Product Details

- Increase the Versatility of Existing Mounting Equipment
- Ideal for Direct Mounting to Standard Breadboards
- Counterbored 1/4-20 or M6 x 1.0 Holes/Slots

TECHSPEC® Slotted 2" x 3" Base Plates are versatile mounting surfaces for breadboard and optical rail applications. Three 6.4mm diameter counterbored holes, ideal for 1/4"-20 hardware, allow posts or post holders to be mounted directly and can also accommodate a variety of other optomechanical components. The plates are ideal for adding extra versatility and adjustment capability to a benchtop optical system. TECHSPEC® Slotted 2" x 3" Base Plates are available in standard sliding or side to side sliding configurations, allowing for adjustment along or perpendicular to the optical axis of the system.

## Technical Information

